Quick Start (Rio Ro Xtended)

1. Unbox & Setup

- show a diagram of the printer and how things are physically setup

2. Install the driver

- screen shots for driver install

3. Design your card

- get your cards
- dimensions for printing
- templates are located on back of card
- front and back pages are important

4. Setup the driver

- colour or monochrome?
- set the slider
- front and back settings
- heat settings + other


5. Print

- print the card
- how to load the cards
- all done



Card Design

- templates & ideas for card designs
- maybe show all template options, including break off cards and then some examples
- have nice headings for each template type



Models & Technical Support

Printer Specifications

Print mode	Long format color dye sublimation and monochrome thermal printing.		
Print area	• Color single-print mode: 3.38 x 2.12" / 3.38 x 1.97"		
	 Color double-print mode (2 passes): 4.33 x 2.12" / 4.33 x 1.97" 		
	• Monochrome: 5.51 x 2.12" / 5.51 x 1.97"		
Warranty**	3 years UltraCoverPlus warranty and support which includes full printhead coverage and free loaner service - Available in North America, EU and other selected territories. Elsewhere 2 years limited depot warranty.		
Card security	A HoloKote security watermark can be printed. A choice of 4 standard HoloKote designs and 1 standard HoloKote Flex design are selectable from the printer driver. For added security, Custom HoloKote enables customization of the watermark to an individual logo or security design.		
Card encoding options	Magnetic stripe encoding. HiCo and LoCo encoder ISO 7811. Smart card encoding: Contact chip, MIFARE, DESFire and iClass.		
Printer interfaces	USB and Ethernet both fitted as standard.		
Software drivers	Windows 2000 Professional (SP4), XP, Vista and 7 (32/64 bit compatible), Windows Server 2003 R2 SP2, Server 2008 (32/64 bit compatible).		
Card capacity	100-card Xtended adjustable feeder (3.38-5.51 x 2.12"), 70-card Xtended stacker (5.51 x 2.12" card capacity).		
Power source	External power supply 100-240V 50-60Hz autoranging.		
Dimensions / weight	24.1" L x 8.6" W x 9.8" H including feeder and stacker. / 10.9 lbs.		
Print speed	†Color standard mode: 31 seconds, †Color fast mode: 23 seconds, †Monochrome resin: 6 seconds (3.38 x 2.12" print area†).		
Operating environment	Sheltered office environment 50°F to 85°F (10°C to 30°C).		

Consumables		PART NUMBERS
Dye films	YMCKO 5 panel dye film, 300 images.	MA300YMCKO
	Monochrome resin black dye film, 1000 images. Also available in *White, *Blue, *Red, *Gold and *Silver.	MA1000K-Black*
Cleaning kit	10 cleaning cards, 1 pen.	3633-0053
Cleaning roller kit	5 cleaning rollers, 1 metal roller bar.	3633-0054
Card types/thickness	Blank or pre-printed Xtended cards: 4.33 x 2.12", 5.51 x 2.12". CR80/CR79 PVC ISO blank, HiCo magnetic stripe, smart cards, self-adhesive, rewritable and HoloPatch cards. 0.51mm to 1.27mm (20mil to 50mil).	
Xtended cards	1000 blank Xtended cards 4.33 x 2.12"	M9007-432
	1000 blank Xtended cards 5.51 x 2.12"	M9007-433

Variants

Rio Pro Xtended	Magicard Rio Pro Xtended Printer 2.12" card width.	3652-0008
Rio Pro Xtended 50	Magicard Rio Pro Xtended Printer 1.97" card width.	3652-0009

Options

Custom HoloKote kit Kit contains a CD to install the data and a Custom HoloKote card that fits into your printer. HoloSet

"For more information or assistance please contact technical support at one of our global offices:"

Ultra Electronics Card Systems Inc.
North American Sales & Support Center

6711 - 176th Avenue NE Redmond, WA 98052

Toll free: 877 236 0933 Tel: +1 (425) 556 9708 Fax: +1 (425) 556 3962

Email: americas@magicard.com

Ultra Electronics Card Systems

Hampshire Road, Weymouth, Dorset DT4 9XD, United Kingdom **Tel**: +44 (0) 1305 767 100

Fax: +44 (0) 1305 777 904 Email: info@magicard.com





